



WALL



WALL è il termoventilatore a parete di JOHNSON Elettrodomestici con due selezioni di potenza, 1000 - 2000W, è ideale per avere un riscaldamento veloce dei locali ed assicurare un tepore uniforme.
Facile da usare grazie al telecomando che non obbliga a toccare l'apparecchio durante il suo funzionamento anche negli ambienti con elevata umidità.
WALL possiede un timer giornaliera di 12 ore inoltre dà la possibilità di programmare ora, giorno e settimana di accensione per avere un ambiente caldo e confortevole quando più lo si desidera.
WALL possiede un display LED digitale, ha la funzione di riconoscimento della finestra aperta, riscalda fino a 20 metri quadri ed è dotato di un filtro antipolvere.



WALL is the wall-mounted fan heater by JOHNSON Elettrodomestici with two power selections, 1000 - 2000W, it is ideal for quickly heating rooms and ensuring uniform warmth.
Easy to use thanks to the remote control that does not require touching the appliance during operation even in environments with high humidity.
WALL has a 12-hour daily timer and also gives the possibility of programming the time, day and week of switching on to have a warm and comfortable environment when you want it most.
WALL has a digital LED display, has the open window recognition function, heats up to 20 square meters and is equipped with a dust filter.



GIFT BOX		MASTER CARTON			PALLET	CONTAINER		
Size (mm)	Kg	Size (mm)	Pcs	Kg	Pcs	20	40	40HQ
500 x 120 x 195	2.3	520 x 250 x 405	4	9.8	96	2148	4296	4940



SCHEDA PRODOTTO
 PRODUCT DETAILS

WALL

FAMILY	HEATING
CODE	WALL
COD. EAN	8008523013684
COD. ITF	18008523013681

CARATTERISTICHE		FEATURES	
Potenza 1000 - 2000 W Aria tiepida 1000 W Aria calda 2000 W Spa luminosa Possibilità di programmare: ora, giorno, settimana di accensione Funzione finestra aperta Display LED con icone di riferimento Alta efficienza termica Filtro antipolvere Telecomando Alimentazione 220-240V ~ 50 Hz		Power 1000 - 2000 W Warm air 1000 W Hot air 2000 W Bright spa Possibility to program: time, day, week of switching on Open window function LED display with reference icons High thermal efficiency Dust filter Remote control Power supply 220-240V ~ 50 Hz	
Dimensioni prodotto:	435 x 110 x 185 mm	Product dimensions:	435 x 110 x 185 mm
Dimensioni imballo:	500 x 120 x 195 mm	Package dimensions:	500 x 120 x 195 mm
Peso imballo + prodotto:	2.3 Kg	Packaging weight + product:	2.3 Kg
Pezzi x master	4 pz	Master pieces:	4 pz
Dimensioni master:	520 x 250 x 405 mm	Master size:	520 x 250 x 405 mm
Peso master:	9.8 Kg	Master Weight:	9.8 Kg
Pezzi x pallet:	96	Pieces for pallet:	96
Altezza pallet:	180 cm	Height pallet:	180 cm
Peso pallet:	245 Kg	Weight pallet:	245 Kg
Colli per strato:	6	Necks per layer:	6
Strati:	4	Layers:	4
Container 20:	2148 pz	Container 20:	2148 pz
Container 40:	4296 pz	Container 40:	4296 pz
Container 40 HQ :	4940 pz	Container 40 HQ:	4940 pz
Codice certificazione:	KPT-2000B 4501L	Certification Code:	KPT-2000B 4501L

TELECOMANDO



SCHERMO LED

